

GRTS Survey Designs for a Finite Resource

Thomas Kincaid

May 24, 2012

Contents

1 Preliminaries	1
2 Shapefile attribute data	2
3 Unstratified, equal probability, GRTS survey design	3
4 Stratified, equal probability, GRTS survey design	6
5 Unstratified, unequal probability, GRTS survey design with an oversample	9
6 Unstratified, unequal probability, GRTS survey design with an oversample and a panel structure for survey over time	11

1 Preliminaries

This document presents example GRTS survey designs for a finite resource. The finite resource used in the designs is lakes in the New England region of the U.S. Four survey designs will be presented: (1) an unstratified, equal probability design; (2) a stratified, equal probability design; (3) an unstratified, unequal probability design with an oversample; and (4) an unstratified, unequal probability design with an oversample and a panel structure for survey over time. The sampling frame used for the survey designs is contained in either an ESRI shapefile, a data frame, or an sp package object. The frame contains the coordinates for a set of points that define the finite resource in addition to attribute data associated with the points. The coordinate system for the set of points in the sampling frame is an equal area projection rather than latitude and longitude. An equal area projection is used so that calculation of distance between points is valid. Use of the three sources for the sampling frame will be illustrated in the example survey designs.

The initial step is to use the library function to load the spsurvey package. After the package is loaded, a message is printed to the R console indicating that the spsurvey package was loaded successfully.

Load the spsurvey package

```
> # Load the spsurvey package
> library(spsurvey)
>
```

Version 2.1 of the spsurvey package was loaded successfully.

2 Shapefile attribute data

The next step is to read the attribute data from the shapefile. The read.dbf function in the spsurvey package is used to read the attribute (dbf) file in the shapefile and assign it to a data frame named att. The initial six lines in the att data frame are printed using the head function.

Two attributes, state name and lake area category, that will be used to define, respectively, stratum codes and unequal selection probability (multidensity) categories for the survey designs are examined. State name is contained in a variable named "state", and lake area category is contained in a variable named "area_cat". For lake area category, lakes are classified by surface area measured in hectares. The table and addmargin functions are used to produce a table displaying number of lakes for each combination of values for the strata and multidensity category variables.

Read the attribute table from the shapefile

```
> # Read the attribute table from the shapefile
> att <- read.dbf("reg1_lakes")
>
```

Display the initial six lines in the attribute data frame

```
> # Display the initial six lines in the attribute data frame
> head(att)
```

	lat_dd	lon_dd	xcoord	ycoord	state	area_cat
1	47.4	-69.2	2005501	2997939	ME	(1,5]
2	47.4	-69.0	2020520	2998539	ME	(1,5]
3	47.3	-69.1	2021486	2990894	ME	(500,7e+04]
4	47.4	-69.1	2013772	2995782	ME	(10,50]
5	47.3	-69.1	2017393	2993215	ME	(5,10]
6	47.3	-69.1	2016111	2992918	ME	(1,5]

>

Display number of lakes cross-classified by the strata and multidensity category variables

```
> # Display number of lakes cross-classified by the strata and multidensity
> # category variables
> addmargins(table("State"=att$state, "Lake Area Category"=att$area_cat))
```

	Lake Area Category						
State	(1,5]	(10,50]	(5,10]	(50,500]	(500,7e+04]	[0,1]	Sum
CT	1181	284	270	90	4	483	2312
MA	1658	693	545	209	6	194	3305
ME	1792	1044	693	656	137	202	4524
NH	765	406	331	167	13	43	1725
RI	256	108	85	41	3	11	504
VT	418	138	137	52	12	46	803
Sum	6070	2673	2061	1215	175	979	13173

>

Lakes in the New England region are displayed in Figure 1. The plot function is used to produce the figure.

```
> plot(att$xcoord, att$ycoord, xlab="x-coordinate", ylab="y-coordinate", pch=20,
+       cex=0.1, col="red")
```

3 Unstratified, equal probability, GRTS survey design

The first survey design is an unstratified, equal probability design. The `set.seed` function is called so that, if necessary, the designs can be replicated.

The initial step is to create a list named `Equaldsgn` that contains information for specifying the survey design. Since the survey design is unstratified, the list contains a single item named "None" that also is a list. The "None" list includes two items: `panel`, which is used to specify the sample size for each panel, and `seltype`, which is used to input the type of random selection for the design. For this example, `panel` is assigned a single value named "PanelOne" that is set equal to 300, and `seltype` is assigned the value "Equal", which indicates equal probability selection.

The `grts` function in the `spsurvey` package is called to select the survey design. The following arguments are included in the call to `grts`: (1) `design`: the named list of stratum design specifications, which is assigned the `Equaldsgn` list; (2) `DesignID`: name for the design, which




Figure 1: Lakes in the New England Region.

is used to create a site ID for each site and is assigned the value "EQUAL"; (3) type.frame: the type of frame, which is assigned the value "finite" to indicate a finite resource; (4) src.frame: source of the frame, which is assigned the value "shapefile" to indicate a shapefile frame; (5) in.shape: name of the input shapefile, which is assigned the value "reg1_lakes"; (6) att.frame: the data frame of attributes associated with elements in the frame, which is assigned the att data frame; and (7) shapefile: option to create a shapefile containing the survey design information, which is assigned FALSE.

During execution of the grts function, messages are printed that indicate the initial number of hierarchical levels used for the GRTS grid, the current number of levels, and the final number of levels. The set of messages is printed for each stratum, and is labeled with the stratum name. For this example, the set of messages is labeled "None", i.e., the name used in the Equaldsgn list. Upon completion of the call to grts, the initial six sites for the survey design and a design summary are printed.

Call the set.seed function so that the design can be replicated

```
> # Call the set.seed function so that the survey designs can be replicate
> set.seed(4447864)
>
```

Create the design list

```
> # Create the design list
> Equaldsgn <- list(None=list(panel=c(PanelOne=300), seltype="Equal"))
>
```

Select the sample

```
> Equalsites <- grts(design=Equaldsgn,
+                   DesignID="EQUAL",
+                   type.frame="finite",
+                   src.frame="shapefile",
+                   in.shape="reg1_lakes",
+                   att.frame=att,
+                   shapefile=FALSE)
```

Stratum: None

Initial number of levels: 5

Current number of levels: 5

Current number of levels: 7

Final number of levels: 7

Print the initial six lines of the survey design

```
> # Print the initial six lines of the survey design
> head(Equalsites@data)
```

	siteID	xcoord	ycoord	mdcaty	wgt	stratum	panel	EvalStatus	EvalReason
1	EQUAL-001	2002873	2980126	Equal	43.9	None	PanelOne	NotEval	
2	EQUAL-002	2051755	2787941	Equal	43.9	None	PanelOne	NotEval	
3	EQUAL-003	2009584	2370445	Equal	43.9	None	PanelOne	NotEval	
4	EQUAL-004	1993945	2420687	Equal	43.9	None	PanelOne	NotEval	
5	EQUAL-005	1901755	2536905	Equal	43.9	None	PanelOne	NotEval	
6	EQUAL-006	1992222	2936987	Equal	43.9	None	PanelOne	NotEval	

	lat_dd	lon_dd	xcoord.1	ycoord.1	state	area_cat
1	47.3	-69.3	2002873	2980126	ME	(1,5]
2	45.5	-69.4	2051755	2787941	ME	(10,50]
3	42.0	-71.3	2009584	2370445	MA	(1,5]
4	42.4	-71.3	1993945	2420687	MA	(1,5]
5	43.7	-72.1	1901755	2536905	NH	(5,10]
6	46.9	-69.6	1992222	2936987	ME	(1,5]

```
>
```

Print the survey design summary

```
> # Print the survey design summary
> dsngsum(Equalsites)
```

Design Summary: Number of Sites

stratum	
None	Sum
300	300

```
>
```

4 Stratified, equal probability, GRTS survey design

The second survey design is a stratified, equal probability design. The state attribute is used to identify strata. List Stratdsgn is assigned design specifications. Stratdsgn includes six lists, one for each stratum. The names for the lists match the levels of the stratum variable, i.e., the unique values of the state attribute. Each list in Stratdsgn contains two items: panel and seltype. The value for panel is the same as the equal probability design (50), and seltype is assigned "Equal".

For this survey design, a data frame will be used as the sampling frame. Since it includes spatial coordinates, the att data frame will be used as the frame. The following arguments are included in the call to grts: (1) design: assigned the Stratdsgn list; (2) DesignID: assigned the value "STRATIFIED"; (3) type.frame: assigned the value "finite"; (4) src.frame: assigned the value "att.frame" to indicate that the sampling frame is provided by argument att.frame; (5) att.frame: assigned the att data frame; (6) xcoord: name of the column in the attributes data frame that identifies x-coordinates, which is assigned the value "xcoord"; (7) ycoord: name of the column in the attributes data frame that identifies y-coordinates, which is assigned the value "ycoord"; (8) stratum: name of the column in the attributes data frame that identifies the stratum code for each element in the frame, which is assigned the value "state"; and (9) shapefile: assigned the value FALSE. Upon completion of the call to grts, the initial six sites for the survey design and a design summary are printed.

Create the design list

```
> Stratdsgn <- list(CT=list(panel=c(PanelOne=50), seltype="Equal"),
+                   MA=list(panel=c(PanelOne=50), seltype="Equal"),
+                   ME=list(panel=c(PanelOne=50), seltype="Equal"),
+                   NH=list(panel=c(PanelOne=50), seltype="Equal"),
+                   RI=list(panel=c(PanelOne=50), seltype="Equal"),
+                   VT=list(panel=c(PanelOne=50), seltype="Equal"))
```

Select the sample

```
> Stratsites <- grts(design=Stratdsgn,
+                   DesignID="STRATIFIED",
+                   type.frame="finite",
+                   src.frame="att.frame",
+                   att.frame=att,
+                   xcoord="xcoord",
+                   ycoord="ycoord",
+                   stratum="state",
+                   shapefile=FALSE)
```

Stratum: CT

Current number of levels: 3

Current number of levels: 4

Current number of levels: 5

Final number of levels: 5

Stratum: MA

Current number of levels: 3

Current number of levels: 5

Final number of levels: 5

Stratum: ME
 Current number of levels: 3
 Current number of levels: 5
 Final number of levels: 5

Stratum: NH
 Current number of levels: 3
 Current number of levels: 5
 Final number of levels: 5

Stratum: RI
 Current number of levels: 3
 Current number of levels: 5
 Final number of levels: 5

Stratum: VT
 Current number of levels: 3
 Current number of levels: 5
 Final number of levels: 5

Print the initial six lines of the survey design

```
> # Print the initial six lines of the survey design
> head(Stratsites@data)
```

	siteID	xcoord	ycoord	mdcaty	wgt	stratum	panel	EvalStatus
1	STRATIFIED-001	1869859	2236177	Equal	46.2	CT	PanelOne	NotEval
2	STRATIFIED-002	1911013	2313970	Equal	46.2	CT	PanelOne	NotEval
3	STRATIFIED-003	1906694	2282263	Equal	46.2	CT	PanelOne	NotEval
4	STRATIFIED-004	1930344	2294624	Equal	46.2	CT	PanelOne	NotEval
5	STRATIFIED-005	1851656	2238601	Equal	46.2	CT	PanelOne	NotEval
6	STRATIFIED-006	1872474	2255853	Equal	46.2	CT	PanelOne	NotEval
	EvalReason	lat_dd	lon_dd	xcoord.1	ycoord.1	area_cat		
1		41.1	-73.3	1869859	2236177	(10,50]		
2		41.7	-72.6	1911013	2313970	(1,5]		
3		41.4	-72.8	1906694	2282263	(10,50]		
4		41.5	-72.5	1930344	2294624	(1,5]		
5		41.2	-73.5	1851656	2238601	(1,5]		
6		41.3	-73.3	1872474	2255853	(1,5]		

>

Print the survey design summary


```
> # Print the survey design summary
> dsgnsum(Stratsites)
```

Design Summary: Number of Sites

```
stratum
  CT  MA  ME  NH  RI  VT Sum
  50  50  50  50  50  50 300
```

```
>
```

5 Unstratified, unequal probability, GRTS survey design with an oversample

The third survey design is an unstratified, unequal probability design with an oversample. Lake area classes are used to identify multidensity categories. List Unequaldsgn is assigned design specifications. Since the survey design is unstratified, Unequaldsgn includes a single list named "None" that contains four items: panel, seltype, caty.n, and over. The value for panel is the same as the equal probability design, and seltype is assigned "Unequal" to indicate unequal selection probabilities. The third item, caty.n, assigns sample sizes for each of the six multidensity categories. Note that the sum of sample sizes provided in caty.n must equal the value in panel. The fourth item, over, is assigned the value 120, which specifies an oversample of 120 sites. An oversample is replacement sites for the survey design. The grts function attempts to distribute the oversample proportionately among sample sizes for the multidensity categories. If the oversample proportion for one or more categories is not a whole number, a warning message is printed and the proportion is rounded to the next higher integer. For this example, the oversample is proportionate to the category sample sizes, and the warning message is not printed.

For this survey design, an sp package object will be used as the sampling frame. The read.shape function will be used to read the shapefile and assign its output to an sp object named shp. The following arguments are included in the call to grts: (1) design: assigned the Unequaldsgn list; (2) DesignID: assigned the value "UNEQUAL"; (3) type.frame: assigned the value "finite"; (4) src.frame: assigned the value "sp.object" to indicate that the sampling frame is provided by an sp object; (5) sp.object: name of the sp object, which is assigned the shp object; (6) att.frame: assigned the att data frame; (7) mdcaty: name of the column in the attributes data frame that identifies the unequal probability category for each element in the frame, which is assigned the value "area_cat"; (8) shapefile: assigned the value FALSE. Upon completion of the call to grts, the initial six sites for the survey design and a design summary are printed.

Create the design list

```
> Unequaldsgn <- list(None=list(panel=c(PanelOne=300),
+                               seltype="Unequal",
+                               caty.n=c("[0,1]"=50, "(1,5]"=50, "(5,10]"=50,
+                                       "(10,50]"=50, "(50,500]"=50,
+                                       "(500,7e+04]"=50),
+                               over=120))
```

Read the shapefile

```
> # Read the shapefile
> shp <- read.shape("reg1_lakes")
>
```

Select the sample

```
> Unequalsites <- grts(design=Unequaldsgn,
+                      DesignID="UNEQUAL",
+                      type.frame="finite",
+                      src.frame="sp.object",
+                      sp.object=shp,
+                      att.frame=att,
+                      mdcaty="area_cat",
+                      shapefile=FALSE)
```

Stratum: None

```
Initial number of levels: 5
Current number of levels: 5
Current number of levels: 7
Current number of levels: 8
Final number of levels: 8
```

Print the initial six lines of the survey design

```
> # Print the initial six lines of the survey design
> head(Unequalsites@data)
```

	siteID	xcoord	ycoord	mdcaty	wgt	stratum	panel	EvalStatus
1	UNEQUAL-001	2118352	2376705	[0,1]	19.6	None	PanelOne	NotEval
2	UNEQUAL-002	1950763	2416446	(10,50]	53.5	None	PanelOne	NotEval
3	UNEQUAL-003	2067486	2816127	(1,5]	121.4	None	PanelOne	NotEval
4	UNEQUAL-004	2043705	2676363	(500,7e+04]	3.5	None	PanelOne	NotEval
5	UNEQUAL-005	1873327	2241300	[0,1]	19.6	None	PanelOne	NotEval

```

6 UNEQUAL-006 1925486 2336149      [0,1]  19.6    None PanelOne    NotEval
  EvalReason lat_dd lon_dd xcoord.1 ycoord.1 state
1          41.8  -70.0  2118352  2376705    MA
2          42.5  -71.9  1950763  2416446    MA
3          45.7  -69.1  2067486  2816127    ME
4          44.5  -69.9  2043705  2676363    ME
5          41.2  -73.3  1873327  2241300    CT
6          41.9  -72.4  1925486  2336149    CT

```

```
>
```

Print the survey design summary

```

> # Print the survey design summary
> dsgnsum(Unequalsites)

```

Design Summary: Number of Sites Classified by mdcaty (Multidensity Category) and panel

	panel		
mdcaty	OverSamp	PanelOne	Sum
(1,5]	19	55	74
(10,50]	28	53	81
(5,10]	21	44	65
(50,500]	18	51	69
(500,7e+04]	15	50	65
[0,1]	19	47	66
Sum	120	300	420

```
>
```

6 Unstratified, unequal probability, GRTS survey design with an oversample and a panel structure for survey over time

The fourth survey design is an unstratified, unequal probability design with an oversample and a panel structure for survey over time. List `Paneldsgn` is assigned design specifications. Since the survey design is unstratified, `Paneldsgn` includes a single list named "None" that contains four items: `panel`, `seltype`, `caty.n`, and `over`. A vector identifying sample sizes for five panels is assigned to `panel`. The value "Unequal" is assigned `seltype`, which indicates unequal selection probabilities. The third item, `caty.n`, assigns sample sizes for each of

six multidensity categories, where lake area classes are used as the categories. The value 100 is assigned to over, which specifies an oversample of 100 sites. For this example, the oversample is not proportionate to the category sample sizes, and the warning message is printed by calling the warnings function.

For this survey design, a shapefile will be used as the sampling frame. The following arguments are included in the call to grts: (1) design: assigned the Paneldsn list; (2) DesignID: assigned the value "UNEQUAL"; (3) type.frame: assigned the value "finite"; (4) src.frame: assigned the value "shapefile"; (5) in.shape: assigned the value "reg1_lakes"; (6) att.frame: assigned the att data frame; (7) mdcaty: assigned the value "area_cat"; and (8) shapefile: assigned the value FALSE. Upon completion of the call to grts, the initial six sites for the survey design and a design summary are printed.

Create the design list

```
> Paneldsn <- list(None=list(panel=c(Annual=50, Year1=50, Year2=50, Year3=50,
+                                     Year4=50, Year5=50),
+                                     seltype="Unequal",
+                                     caty.n=c("[0,1]"=50, "(1,5]"=50, "(5,10]"=50,
+                                               "(10,50]"=50, "(50,500]"=50,
+                                               "(500,7e+04]"=50),
+                                     over=100))
```

Select the sample

```
> Panelsites <- grts(design=Paneldsn,
+                     DesignID="UNEQUAL",
+                     type.frame="finite",
+                     src.frame="shapefile",
+                     in.shape="reg1_lakes",
+                     att.frame=att,
+                     mdcaty="area_cat",
+                     shapefile=FALSE)
```

Stratum: None

Initial number of levels: 5

Current number of levels: 5

Current number of levels: 7

Current number of levels: 8

Final number of levels: 8

Print the warning message

```
> # Print the warning message
> warnings()
>
```

Warning message:

```
In grts(design = Paneldsgn, DesignID = "UNEQUAL", type.frame = "finite", :
```

Oversample size is not proportional to category sample sizes for stratum "None".

Print the initial six lines of the survey design

```
> # Print the initial six lines of the survey design
> head(Panelsites@data)
```

	siteID	xcoord	ycoord	mdcaty	wgt	stratum	panel	EvalStatus
1	UNEQUAL-001	2085642	2633214	[0,1]	19.6	None	Annual	NotEval
2	UNEQUAL-002	2043490	2785734	(500,7e+04]	3.5	None	Annual	NotEval
3	UNEQUAL-003	2021486	2990894	(500,7e+04]	3.5	None	Annual	NotEval
4	UNEQUAL-004	1987175	2419772	(10,50]	53.5	None	Annual	NotEval
5	UNEQUAL-005	2090281	2730607	[0,1]	19.6	None	Annual	NotEval
6	UNEQUAL-006	2093807	2874103	(5,10]	41.2	None	Annual	NotEval

	EvalReason	lat_dd	lon_dd	xcoord.1	ycoord.1	state
1		44.1	-69.5	2085642	2633214	ME
2		45.5	-69.5	2043490	2785734	ME
3		47.3	-69.1	2021486	2990894	ME
4		42.5	-71.4	1987175	2419772	MA
5		44.9	-69.1	2090281	2730607	ME
6		46.1	-68.6	2093807	2874103	ME

>

Print the survey design summary

```
> # Print the survey design summary
> dsgnsum(Panelsites)
```

Design Summary: Number of Sites Classified by mdcaty (Multidensity Category) and panel

	panel								
mdcaty	Annual	OverSamp	Year1	Year2	Year3	Year4	Year5	Sum	
(1,5]	10	15	7	12	11	5	6	66	
(10,50]	8	19	6	9	7	14	12	75	
(5,10]	6	17	10	8	6	5	4	56	
(50,500]	9	19	6	4	6	10	7	61	
(500,7e+04]	7	13	10	8	11	6	10	65	
[0,1]	10	19	11	9	9	10	11	79	
Sum	50	102	50	50	50	50	50	402	

>